#### Regulation EC No 1907/2006 Art.31

**Productname:** FLAW DETECTOR PENETRANT 2

**Ref.Nr.:** BDS001088\_3\_20120109

Creationdate : Replaces:

09.01.12 Version: 1.0

UK10068

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

#### **FLAW DETECTOR PENETRANT 2**

Aerosol

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Welding Products

#### 1.3. Details of the supplier of the safety data sheet

CRC Industries UK Ltd.
Ambersil House - Wylds Road
Castlefield Industrial Estate
TA6 4DD Bridgwater Somerset
United Kingdom

Tel.: +44 1278 727200 Fax.: +44 1278 425644 E-mail : hse.uk@crcind.com

#### 1.4. Emergency telephone number

(+44)(0)1278 72 7200

# SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

# Classification according to 67/548/EEC or 1999/45/EC:

**Health:** R66: Repeated exposure may cause skin dryness or cracking.

Physical: EXTREMELY FLAMMABLE

**Environment:** R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in

the aquatic environment.

# 2.2. Label elements

Warning symbol(s): EXTREMELY FLAMMABLE



**Risk-phrase(s):** R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in

the aquatic environment.



#### Regulation EC No 1907/2006 Art.31

Productname: FLAW DETECTOR PENETRANT 2 Creationdate: 09.01.12 Version: 1.0

**Ref.Nr.:** BDS001088\_3\_20120109 **Replaces:** UK10068

R66: Repeated exposure may cause skin dryness or cracking.

Safety-phrase(s): S2: Keep out of the reach of children.

S16: Keep away from sources of ignition - No smoking.

S23: Do not breathe vapours/spray. S24/25: Avoid contact with skin and eyes.

S35: This material and its container must be disposed of in a safe way.

S51: Use only in well-ventilated areas.

Special labelling provisions: Contains:

N-(2-ethylhexyl)-1-[[3-methyl-4-[(3 methylphenyl)azo]phenyl]azo] naphthalen-

2-amine

May produce an allergic reaction.

Extra label elements according Pressurised container: protect from sunlight and do not expose to

to Aerosol Dispenser Directive temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not

**75/324/EC:** spray on a naked flame or any incandescent material.

Without adequate ventilation formation of explosive mixtures may be possible.

Other extra label elements: Remark: Preparations classified as harmful on the basis of an aspiration

hazard need not be labelled as harmful with R65 when placed on the market in aerosol containers or in containers fitted with a sealed spray attachment. (EU-

Directive 67/548 Annex VI 9.4)

#### 2.3. Other hazards

None

# SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable.

#### 3.2. Mixtures

Hazardous ingredient	CAS-nr.	EC-nr	w/w %	symbol	R-phrases*	Notes
Hydrocarbons,C3-4-rich, petroleum distillate Petroleumgas (1,3-butadiene < 0.1%)	68512-91- 4	270-990- 9	<mark>50-75</mark>	F+	12	K
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics	-	926-141- 6	<mark>25-50</mark>	Xn	65-66	
Solvent naphtha (petroleum), heavy arom. (benzene<0.1%)	64742-94- 5	265-198- 5	1-5	Xn,N	51/53-65-66- 67	В
alcohols, C9-11, ethoxylated	68439-46- 3		<5	Xn	22-41	
(Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine	110-25-8	203-749- 3	<1	Xi,N	38-41-50/53	
N-(2-ethylhexyl)-1-[[3-methyl-4-[(3 methylphenyl)azo]phenyl]azo] naphthalen- 2-amine	56358-10- 2	260-125- 3	<1	Xi	38-43	
Explanation notes						
B : substance with national established workplace exposure limit						
K : not classified as carcinogen, less than 0.1% w/w 1,3-butadiene (Einecs-nr. 203-450-8)						

Hazardous ingredient Registration CAS- EC-nr w/w Hazard Class and Hazard Notes



#### Regulation EC No 1907/2006 Art.31

Productname: FLAW DETECTOR PENETRANT 2 Creationdate: 09.01.12 Version: 1.0

**Ref.Nr.:** BDS001088\_3\_20120109 **Replaces:** UK10068

	number	nr.		%	Category	statement	
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics	01-2119456620- 43	-	926- 141-6	25- 50	Asp. Tox. 1	H304	

<sup>(\*</sup> Explanation phrases : see chapter 16)

# **SECTION 4: First aid measures**

# 4.1. Description of first aid measures

Contact with eyes: If substance has got into eyes, immediately wash out with plenty of water

Seek medical attention if irritation persists

Contact with skin: Wash with water and soap.

Seek medical attention if irritation persists

Inhalation: Fresh air, keep warm and at rest.

Seek medical attention if ill effects occur

**Ingestion:** Ingestion is unlikely to occur

If swallowed do not induce vomiting because of risk of aspiration into the lungs. If aspiration is suspected obtain immediate medical attention

## 4.2. Most important symptoms and effects, both acute and delayed

**Inhalation:** Excessive inhalation of solvent vapours may give rise to nausea, headaches

and dizziness

**Ingestion:** After vomiting of swallowed product aspiration into lungs is likely. Solvents

may induce chemical pneumonia.

Symptoms: sore throat, abdominal pain, nausea, vomiting

**Skin contact :** May cause irritation.

Symptoms: redness and pain

**Eye contact :** May cause irritation.

Symptoms: redness and pain

#### 4.3. Indication of any immediate medical attention and special treatment needed

**General Advice:** If you feel unwell, seek medical advice (show the label where possible

If symptoms persist always call a doctor

# SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

foam, carbon dioxide or dry agent

#### 5.2. Special hazards arising from the substance or mixture

Aerosols may explode if heated above 50°C Forms hazardous decomposition products CO.CO2

### 5.3. Advice for firefighters



#### Regulation EC No 1907/2006 Art.31

**Productname:** FLAW DETECTOR PENETRANT 2

**Ref.Nr.:** BDS001088\_3\_20120109

Creationdate : Replaces:

09.01.12 Version: 1.0

UK10068

Keep container(s) exposed to fire cool, by spraying with water In case of fire, do not breathe fumes

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Shut off all ignition sources
Ensure adequate ventilation
Wear suitable protective clothing and gloves.

#### 6.2. Environmental precautions

Do not allow to enter public sewers and watercourses

If polluted water reaches drainage systems or water courses, immediately inform appropriate authorities

# 6.3. Methods and material for containment and cleaning up

Absorb spillage in suitable inert material

#### 6.4. Reference to other sections

For further information see section 8

# SECTION 7: Handling and storage

# 7.1. Precautions for safe handling

Keep away from heat and sources of ignition

Take precautionary measures against static discharges

Equipment should be earthed

Use explosion-proof electrical/ventilating/lighting/?/equipment.

Use only non-sparking tools.

Do not breathe aerosols or vapours.

Ensure adequate ventilation

Avoid contact with skin and eyes.

Wash thoroughly after use

Wear protective gloves/protective clothing/eye protection/face protection.

#### 7.2. Conditions for safe storage, including any incompatibilities

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Keep out of reach of children.

#### 7.3. Specific end use(s)

Welding Products

# SECTION 8: Exposure controls/personal protection



#### Regulation EC No 1907/2006 Art.31

**Productname:** FLAW DETECTOR PENETRANT 2

**Ref.Nr.:** BDS001088\_3\_20120109

Creationdate : Replaces:

09.01.12 Version: 1.0

UK10068

#### 8.1. Control parameters

#### **Exposure limits:**

No information available

#### 8.2. Exposure controls

**Control procedures :** Ensure adequate ventilation

Keep away from heat and sources of ignition

Take precautionary measures against static discharges

**Personal protection:** Take precautions to avoid contact with skin and eyes when handling the

product.

Ensure adequate ventilation

**inhalation:** In case of insufficient ventilation, wear suitable respiratory equipment.

Air purifying respirator equiped with organic gas/vapor cartridge (type A or AX)

hands and skin: Wear suitable protective gloves

(nitrile)

eyes: Wear safety goggles.

# SECTION 9: Physical and chemical properties

# 9.1. Information on basic physical and chemical properties

(for aerosols data for the product without propellant)

Apperance: physical state: Propane/butane propelled liquid.

colour: Red. odour : Solvent. pH: Not applicable. Boiling point/range: Not available. >62 °C Flash point: Not available. Evaporation rate: Explosion limits: upper limit: Not available. lower limit: Not available. Not available. Vapour pressure :

**Relative density :** 0.826 g/cm3 (@ 20°C). **Solubility in water :** Emulsifies with water

Auto-ignition: > 200 °C
Viscosity: Not available.

### 9.2. Other information

# SECTION 10: Stability and reactivity

### 10.1. Reactivity

No hazardous reactions known if used for its intended purpose



### Regulation EC No 1907/2006 Art.31

Productname: FLAW DETECTOR PENETRANT 2

Ref.Nr.: BDS001088 3 20120109 Creationdate: Replaces:

09.01.12 Version: 1.0

UK10068

# 10.2. Chemical stability

Stable

# 10.3. Possibility of hazardous reactions

No hazardous reactions known if used for its intended purpose

#### 10.4. Conditions to avoid

Avoid overheating

### 10.5. Incompatible materials

Strong oxidising agent

# 10.6. Hazardous decomposition products

CO,CO2

# **SECTION 11: Toxicological information**

# 11.1. Information on toxicological effects

Inhalation :	Inhalation of solvent vapours may give rise to nausea, headaches and dizziness
Ingestion :	After vomiting of swallowed product aspiration into lungs is likely. Solvents may induce chemical pneumonia.
Skin contact :	Prolonged skin contact will result in defatting of the skin, leading to irritation, and in some cases, dermatitis  Repeated exposure may cause skin dryness or cracking.
Eye contact :	May cause irritation.

# Toxicological data:

Hazardous ingredient	CAS-nr.	method	
Solvent naphtha (petroleum), heavy arom. (benzene<0.1%)	64742-94-5	LD50 oral rat	> 2000 mg/kg
		LD50 derm.rabit	> 2000 mg/kg
alcohols, C9-11, ethoxylated	68439-46-3	LD50 oral rat	1000-1400 mg/kg
		LD50 derm.rabit	>2000 mg/kg

# SECTION 12: Ecological information

# 12.1. Toxicity

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.



Ref.Nr.:

### Regulation EC No 1907/2006 Art.31

**Productname:** FLAW DETECTOR PENETRANT 2

BDS001088\_3\_20120109

Creationdate : Replaces:

09.01.12 Version: 1.0

UK10068

# **Ecotoxicological data:**

Hazardous ingredient	CAS-nr.	method	
alcohols, C9-11, ethoxylated	68439-46-3	LC50 fish	10-100 mg/l
		EC50 daphnia	5-25 mg/l

# 12.2. Persistence and degradability

No experimental data available

#### 12.3. Bioaccumulative potential

No experimental data available

### 12.4. Mobility in soil

Insoluble in water

#### 12.5. Results of PBT and vPvB assessment

No information available

### 12.6. Other adverse effects

# **SECTION 13: Disposal considerations**

# 13.1. Waste treatment methods

**Product :** This material and its container must be disposed of in a safe way.

Do not discharge into drains or the environment, dispose to an authorised

waste collection point.

**Contaminated packaging :** Disposal should be in accordance with local, state or national legislation

# SECTION 14: Transport information

#### 14.1. UN number

UN-number: 1950

#### 14.2. UN proper shipping name

Proper shipping name: AEROSOLS, flammable

#### 14.3. Transport hazard class(es)

Class: 2.1



7/9

# **CRC Industries UK Limited**

#### Regulation EC No 1907/2006 Art.31

**Productname:** FLAW DETECTOR PENETRANT 2

**Ref.Nr.:** BDS001088\_3\_20120109

Creationdate : Replaces:

09.01.12 Version: 1.0

UK10068

ADR/RID - Classification code: 5F

#### 14.4. Packing group

Packing group: Not applicable.

#### 14.5. Environmental hazards

ADR/RID - Environmentally	No
hazardous:	INC
IMDG - Marine pollutant:	No
IATA/ICAO - Environmentally	No
hazardous:	INC

# 14.6. Special precautions for user

ADR/RID - Tunnelcode:	(D)
IMDG - Ems:	F-D,S-U
IATA/ICAO - PAX:	203
IATA/ICAO - CAO	203

# 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

# SECTION 15: Regulatory information

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

The Safety Data Sheet is compiled according to the current European requirements.

Dir. 2008/47/EC amendment of the aerosol dispenser directive 75/324/EEC.

EU-directive 99/45/EC

Regulation (EC) No 1907/2006 (REACH)

# 15.2. Chemical safety assessment

No information available

# SECTION 16: Other information

\*Explanation risk-phrases: R12: Extremely flammable.

R22: Harmful if swallowed.

R38: Irritating to skin.

R41: Risk of serious damage to eyes.

R43: May cause sensitization by skin contact.

R65: Harmful: may cause lung damage if swallowed.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects



#### Regulation EC No 1907/2006 Art.31

FLAW DETECTOR PENETRANT 2 Productname:

Ref.Nr.: BDS001088 3 20120109 Creationdate: Replaces:

09.01.12 Version: 1.0

UK10068

in the aquatic environment.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in

the aquatic environment.

\*Explanation hazard statements: H304: May be fatal if swallowed and enters airways.

This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulation.

The information contained herewith is based on the present state of our knowledge and is intended to describe our products from the point of view of safety requirements. It does not guarantee any specific properties. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC.

