Regulation EC No 1907/2006 Art.31

FLAW DETECTOR DEVELOPER 3 Creationdate: 28.01.20 Version: 2.1 Productname: Ref.Nr.: UDS000718 3 20200128 (EN) Replaces: UDS000718 20191216

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

FLAW DETECTOR DEVELOPER 3

Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

Welding Products

1.3. Details of the supplier of the safety data sheet

CRC Industries UK Ltd. Wylds Road **Castlefield Industrial Estate TA6 4DD Bridgwater Somerset United Kingdom**

Tel.: +44 1278 727200 Fax.: +44 1278 425644 E-mail: hse.uk@crcind.com

1.4. Emergency telephone number

(+44)(0)1278 72 7200 (office hours)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Physical: Aerosols, category 1

Extremely flammable aerosol.

Pressurised container: May burst if heated.

Classification is based on test data.

Health: Eye irritation, category 2

Causes serious eye irritation.

Specific target organ toxicity - single exposure, category 3

May cause drowsiness or dizziness.

Classification based on calculation method. **Environment:** Not classified Classification based on calculation method.

2.2. Label elements



1/10

CRC Industries UK Limited

Ambersil House, Wylds Road, Castlefield Industrial Estate, Bridgwater, Somerset, TA6 4DD
Tel: +44 (0)1278 727200 Fax: +44 (0)1278 425644 web: www.ambersil.com

Regulation EC No 1907/2006 Art.31

 Productname :
 FLAW DETECTOR DEVELOPER 3
 Creationdate :
 28.01.20 Version : 2.1

 Ref.Nr.:
 UDS000718_3_20200128 (EN)
 Replaces:
 UDS000718_20191216

Labelling according to Regulation (EC) No 1272/2008

Product identifier: Contains:

propan-2-ol; isopropyl alcohol; isopropanol

acetone; propan-2-one; propanone

Hazard pictogram(s):

Signal word: Danger

Hazard statement(s): H222 : Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

Precautionary statement(s): P102 : Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P261 : Avoid breathing dust/fume/gas/mist/vapours/spray. P271 : Use only outdoors or in a well-ventilated area.

P410/412: Protect from sunlight. Do not expose to temperatures exceeding

50°C/122°F.

P501-2: Dispose of contents/container to an authorised waste collection point.

2.3. Other hazards

No information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable.

3.2. Mixtures

Hazardous ingredient	Registration number	CAS-nr.	EC-nr	w/w %	Hazard Class and Category	Hazard statement	Notes
Hydrocarbons, C3-4-rich, petroleum distillate Petroleumgas (1,3-butadiene < 0.1%)	01-2119485926- 20	68512- 91-4	270- 990-9	40- 60	Press. Gas, Flam. Gas 1	H280,H220	K,G
propan-2-ol; isopropyl alcohol ;isopropanol	01-2119457558- 25	67-63-0	200- 661-7	10- 30	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3	H225,H319,H336	В
acetone; propan-2-one; propanone	01-2119471330- 49	67-64-1	200- 662-2	10- 30	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3	H225,H319,H336	А
Explanation notes							

A: substance with Community workplace exposure limit

B: substance with national established workplace exposure limit

G: exempted from the obligation to register in accordance with art.2(7)of REACH Regulation No 1907/2006

K: not classified as carcinogen, less than 0.1% w/w 1,3-butadiene (Einecs-nr. 203-450-8)



Tel: +44 (0)1278 727200 Fax: +44 (0)1278 425644 web: www.ambersil.com

Regulation EC No 1907/2006 Art.31

 Productname :
 FLAW DETECTOR DEVELOPER 3
 Creationdate :
 28.01.20 Version : 2.1

 Ref.Nr.:
 UDS000718_3_20200128 (EN)
 Replaces:
 UDS000718_20191216

(* Explanation phrases : see chapter 16)

SECTION 4: First aid measures

4.1. Description of first aid measures

Contact with eyes: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Contact with skin : Take off contaminated clothing and wash before reuse.

IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention.

Inhalation: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER or doctor/physician if you feel unwell.

Ingestion: If swallowed accidentally, do not induce vomiting and seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation: Excessive inhalation of solvent vapours may give rise to nausea, headaches

and dizziness

Ingestion: May cause gastrointestinal disturbances

Symptoms: sore throat, abdominal pain, nausea, vomiting

Skin contact : May cause irritation.

Symptoms: redness and pain

Eye contact: Irritating to eyes

Symptoms: redness and pain

4.3. Indication of any immediate medical attention and special treatment needed

General Advice: If you feel unwell, seek medical advice (show the label where possible

If symptoms persist always call a doctor

SECTION 5: Firefighting measures

5.1. Extinguishing media

foam, carbon dioxide or dry agent

5.2. Special hazards arising from the substance or mixture

Aerosols may explode if heated above 50°C Forms hazardous decomposition products CO,CO2

5.3. Advice for firefighters

Keep container(s) exposed to fire cool, by spraying with water In case of fire, do not breathe fumes



Tel: +44 (0)1278 727200 Fax: +44 (0)1278 425644 web: www.ambersil.com

Regulation EC No 1907/2006 Art.31

 Productname :
 FLAW DETECTOR DEVELOPER 3
 Creationdate :
 28.01.20 Version : 2.1

 Ref.Nr.:
 UDS000718_3_20200128 (EN)
 Replaces:
 UDS000718_20191216

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Shut off all ignition sources
Ensure adequate ventilation
Wear suitable protective clothing and gloves.

6.2. Environmental precautions

Do not allow to enter public sewers and watercourses
If polluted water reaches drainage systems or water courses, immediately inform appropriate authorities

6.3. Methods and material for containment and cleaning up

Absorb spillage in suitable inert material Place in appropriate container

6.4. Reference to other sections

For further information see section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep away from heat and sources of ignition

Take precautionary measures against static discharges

Equipment should be earthed

Use explosion-proof electrical/ventilating/lighting/.../equipment.

Use only non-sparking tools.

Do not breathe aerosols or vapours.

Ensure adequate ventilation

Avoid contact with skin and eyes.

Wash thoroughly after use

Wear protective gloves/protective clothing/eye protection/face protection.

Evewash bottles should be available

7.2. Conditions for safe storage, including any incompatibilities

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Keep out of reach of children.

7.3. Specific end use(s)

Welding Products

SECTION 8: Exposure controls/personal protection



Tel: +44 (0)1278 727200 Fax: +44 (0)1278 425644 web: www.ambersil.com

Regulation EC No 1907/2006 Art.31

FLAW DETECTOR DEVELOPER 3 Creationdate: 28.01.20 Version: 2.1 Productname: Ref.Nr.: Replaces: UDS000718 20191216 UDS000718 3 20200128 (EN)

8.1. Control parameters

Exposure limits:

Hazardous ingredient	CAS-nr.	method	
EU established exposure limits:			
propan-2-ol; isopropyl alcohol ;isopropanol	67-63-0	TWA	400 ppm
		STEL	500 ppm
acetone; propan-2-one; propanone	67-64-1	TWA	500 ppm
National established exposure limits, United Kingdom		-	-
propan-2-ol; isopropyl alcohol; isopropanol	67-63-0	TWA	400 ppm
		STEL	500 ppm
acetone; propan-2-one; propanone	67-64-1	TWA	500 ppm
		STEL	1500 ppm
National established exposure limits, Ireland			
propan-2-ol; isopropyl alcohol ;isopropanol	67-63-0	TWA	200 ppm
		STEL	400 ppm
acetone; propan-2-one; propanone	67-64-1	TWA	500 ppm
		STEL	-

8.2. Exposure controls

Control procedures:

Take precautionary measures against static discharges Personal protection: Take precautions to avoid contact with skin and eyes when handling the product. Ensure adequate ventilation Wear suitable protective gloves In case of insufficient ventilation, wear suitable respiratory equipment. inhalation: recommended respiratory protection: Air purifying respirator equiped with organic gas/vapor cartridge (type A) When handling the product wear chemical-resistant gloves (standard EN 374). hands and skin:

Keep away from heat and sources of ignition

Ensure adequate ventilation

The breakthrough time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be changed part-way through.

Recommended gloves:

Wear safety eyewear according to EN 166. eyes:

Avoid release to the environment. **Environmental protection:**

Collect spillage.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

(for aerosols data for the product without propellant)

Appearance: physical state: Propane/butane propelled liquid.

colour: White. odour: Solvent.



Regulation EC No 1907/2006 Art.31

FLAW DETECTOR DEVELOPER 3 Creationdate: 28.01.20 Version: 2.1 Productname: Ref.Nr.: UDS000718 3 20200128 (EN) Replaces: UDS000718 20191216

pH: Not applicable. Not available. Boiling point/range: Flash point: Not available. Evaporation rate: Not available. **Explosion limits: upper limit:** Not available. lower limit: Not available. Vapour pressure: Not available.

Relative density: 0.885 g/cm3 (@ 20°C). Solubility in water: Insoluble in water Not available. Auto-ignition: Viscosity: Not applicable.

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reactions known if used for its intended purpose

10.2. Chemical stability

Stable

10.3. Possibility of hazardous reactions

No hazardous reactions known if used for its intended purpose

10.4. Conditions to avoid

Avoid overheating

10.5. Incompatible materials

Strong oxidising agent

10.6. Hazardous decomposition products

CO,CO2

SECTION 11: Toxicological information

11.1. Information on toxicological effects

based on available data the classification criteria are not met acute toxicity: skin corrosion/irritation: based on available data the classification criteria are not met

serious eye damage/irritation: Causes serious eye irritation.



Regulation EC No 1907/2006 Art.31

FLAW DETECTOR DEVELOPER 3 Creationdate: 28.01.20 Version: 2.1 Productname: Ref.Nr.: UDS000718_3_20200128 (EN) Replaces: UDS000718 20191216

respiratory or skin sensitisation:	based on available data the classification criteria are not met
germ cell mutagenicity:	based on available data the classification criteria are not met
carcinogenicity:	based on available data the classification criteria are not met
toxicity for reproduction:	based on available data the classification criteria are not met
STOT-single exposure:	May cause drowsiness or dizziness.
STOT repeated exposure:	based on available data the classification criteria are not met
aspiration hazard:	based on available data the classification criteria are not met

Information on likely routes of exposure:

Inhalation: Inhalation of solvent vapours may give rise to nausea, headaches and

dizziness

Ingestion: May cause gastrointestinal disturbances

Skin contact: May cause irritation. Eye contact: Irritating to eyes

Toxicological data:

Hazardous ingredient	CAS-nr.	method	
propan-2-ol; isopropyl alcohol ;isopropanol	67-63-0	LD50 oral rat	5840 mg/kg
		LC50 inhal.rat	> 25000 mg/l
		LD50 derm.rabit	13900 mg/kg
acetone; propan-2-one; propanone	67-64-1	LD50 oral rat	> 5800 mg/kg
		LC50 inhal.rat	76 mg/l
		LD50 derm.rabit	> 15800 mg/kg

SECTION 12: Ecological information

12.1. Toxicity

Not classified

Ecotoxicological data:

Hazardous ingredient	CAS-nr.	method	
propan-2-ol; isopropyl alcohol ;isopropanol	67-63-0	IC50 algae	1000 mg/l
		LC50 fish	9640 mg/l
		EC50 daphnia	9714 mg/l
acetone; propan-2-one; propanone	67-64-1	IC50 algae	530 mg/l
		LC50 fish	5540 mg/l
		EC50 daphnia	8800 mg/l

12.2. Persistence and degradability

No experimental data available



Regulation EC No 1907/2006 Art.31

FLAW DETECTOR DEVELOPER 3 Creationdate: 28.01.20 Version: 2.1 Productname: Ref.Nr.: UDS000718_3_20200128 (EN) Replaces: UDS000718 20191216

12.3. Bioaccumulative potential

No experimental data available

12.4. Mobility in soil

Insoluble in water

12.5. Results of PBT and vPvB assessment

No information available

12.6. Other adverse effects

No information available

GWP (global warming potential): 2

SECTION 13: Disposal considerations

13.1. Waste treatment methods

National regulations: Disposal should be in accordance with local, state or national legislation

SECTION 14: Transport information

14.1. UN number

UN-number: 1950

14.2. UN proper shipping name

AEROSOLS Proper shipping name:

14.3. Transport hazard class(es)

Class: 2.1 ADR/RID - Classification code: 5F

14.4. Packing group

Packing group: Not applicable.

14.5. Environmental hazards

ADR/RID - Environmentally No hazardous: IMDG - Marine pollutant: No No IATA/ICAO - Environmentally



8 / 10

CRC Industries UK Limited

Regulation EC No 1907/2006 Art.31

 Productname :
 FLAW DETECTOR DEVELOPER 3
 Creationdate :
 28.01.20 Version : 2.1

 Ref.Nr.:
 UDS000718_3_20200128 (EN)
 Replaces:
 UDS000718_20191216

hazardous:

14.6. Special precautions for user

ADR/RID - Tunnelcode:	(D)
IMDG - Ems:	F-D, S-U
IATA/ICAO - PAX:	203
IATA/ICAO - CAO	203

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

The Safety Data Sheet is compiled according to the current European requirements.

Regulation (EC) No 1907/2006 (REACH)

Regulation (EC) No 1272/2008 (CLP)

Dir. 2013/10/EU, 2008/47/EC amendment of the aerosol dispenser directive 75/324/EEC.

European data	
Wassergefährdungsklasse	class 1 (self classification, Germany)
Wassergefährdungsklasse	class 1 (self classification, Germany)
Wassergefährdungsklasse	class 1 (self classification, Germany)
Wassergefährdungsklasse	class 1 (self classification, Germany)

15.2. Chemical safety assessment

No information available

SECTION 16: Other information

*Explanation hazard statements: H220: Extremely flammable gas.

H225: Highly flammable liquid and vapour.

H280 : Contains gas under pressure; may explode if heated.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

acronyms and synonyms: TWA = time weight average

STEL = short time exposure limit
VOC = volatile organic compounds
PBT = persistant bioaccumulative toxic

vPvB = very persitant very bioaccumulative

This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulation.

The information contained herewith is based on the present state of our knowledge and is intended to describe our products from the point of view of safety requirements. It does not guarantee any specific properties. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC.



Regulation EC No 1907/2006 Art.31

Productname: FLAW DETECTOR DEVELOPER 3 Creationdate: 28.01.20 Version : 2.1 Ref.Nr.: Replaces: UDS000718_20191216 UDS000718_3_20200128 (EN)

