Safety Data Sheet

Regulation EC No 1907/2006 Art.31

Productname :	Easy Weld
Ref.Nr.:	BDS000994_3_20130306

Creationdate : Replaces: 06.03.13 Version : 2.0 BDS000994_20111209

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Easy Weld Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

Welding Products

1.3. Details of the supplier of the safety data sheet

CRC Industries UK Ltd. Ambersil House - Wylds Road Castlefield Industrial Estate TA6 4DD Bridgwater Somerset United Kingdom Tel.: +44 1278 727200 Fax.: +44 1278 425644 E-mail : hse.uk@crcind.com

1.4. Emergency telephone number

(+44)(0)1278 72 7200

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to 67/548/EEC or 1999/45/EC:

Health:	R67: Vapours may cause drowsiness and dizziness.
Physical:	EXTREMELY FLAMMABLE
Environment:	R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

2.2. Label elements

 Warning symbol(s) :
 EXTREMELY FLAMMABLE

 Image: Symbol (s) :
 R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.



Safety Data Sheet		Regulation EC No 1907/2006 Art.31		
Productname :	Easy Weld	Creationdate :	06.03.13 Version : 2.0	
Ref.Nr.:	BDS000994_3_20130306	Replaces:	BDS000994_20111209	

	R67: Vapours may cause drowsiness and dizziness.
Safety-phrase(s) :	S2: Keep out of the reach of children.
	S16: Keep away from sources of ignition - No smoking.
	S23: Do not breathe vapours/spray.
	S35: This material and its container must be disposed of in a safe way.
	S51: Use only in well-ventilated areas.
Extra label elements accordin	gPressurised container: protect from sunlight and do not expose to
to Aerosol Dispenser Directiv	e temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not
75/324/EC:	spray on a naked flame or any incandescent material.
	Without adequate ventilation formation of explosive mixtures may be possible.
Other extra label elements:	Remark: Preparations classified as harmful on the basis of an aspiration
	hazard need not be labelled as harmful with R65 when placed on the market in
	aerosol containers or in containers fitted with a sealed spray attachment. (EU-
	Directive 67/548 Annex VI 9.4)

2.3. Other hazards

None

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable.

3.2. Mixtures

Hazardous ingredient	CAS-nr.	EC-nr	w/w %	symbol	R-phrases*	Notes
Hydrocarbons,C3-4-rich, petroleum distillate Petroleumgas (1,3-butadiene < 0.1%)	<mark>68512-91-</mark> 4	270-990- 9	60- 100	F+	12	к
Naphtha (petroleum), hydrotreated light	64742-49- 0	931-254- 9	<mark>5-10</mark>	F <mark>,Xn,N</mark>	<mark>11-38-51/53-65-</mark> 67	B,P
pentane	1 <mark>09-66-0</mark>	203-692- 4	<mark>1-5</mark>	F <mark>+,Xn,N</mark>	12-51/53-65-66- 67	A
Explanation notes					'	
A : substance with Community workplace exposure limit						
B : substance with national established workplace exposure limit						
K : not classified as carcinogen, less than 0.1% w/w 1,3-butadiene (Einecs	-nr. 203-450	-8)				
P : not classified as carcinogen, less than 0.1% w/w benzene (Einecs-nr. 2	00-753-7)					

Hazardous ingredient	Registration number	CAS-nr.	EC-nr	w/w %	Hazard Class and Category	Hazard statement	Notes
Naphtha (petroleum), hydrotreated light	01-2119484651- 34	64742- 49-0	931- 254-9	<mark>5-10</mark>	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2	H <mark>225,H315,H336,H304,H411</mark>	B,P
pentane	01-2119459286- 30	109-66- 0	203- 692-4	1-5	Flam. Liq. 2, Asp. Tox. 1, STOT SE 3, Aquatic Chronic 2	H225,H304,H336,H411	A
Explanation notes							

A : substance with Community workplace exposure limit

B : substance with national established workplace exposure limit



Safety Data Sheet		Regulation EC No 1907/2006 Art.31		
Productname :	Easy Weld	Creationdate :	06.03.13 Version : 2.0	
Ref.Nr.:	BDS000994_3_20130306	Replaces:	BDS000994_20111209	

Regulation EC No 1907/2006 Art 31

P : not classified as carcinogen, less than 0.1% w/w benzene (Einecs-nr. 200-753-7)

(* Explanation phrases : see chapter 16)

SECTION 4: First aid measures

4.1. Description of first aid measures

Contact with eyes :	If substance has got into eyes, immediately wash out with plenty of water Seek medical attention if irritation persists
Contact with skin :	Wash with water and soap. Seek medical attention if irritation persists
Inhalation :	Fresh air, keep warm and at rest.
	Seek medical attention if ill effects occur
Ingestion :	If swallowed do not induce vomiting because of risk of aspiration into the lungs. If aspiration is suspected obtain immediate medical attention

4.2. Most important symptoms and effects, both acute and delayed

Inhalation :	Excessive inhalation of solvent vapours may give rise to nausea, headaches and dizziness
Ingestion :	After vomiting of swallowed product aspiration into lungs is likely. Solvents may induce chemical pneumonia. Symptoms : sore throat, abdominal pain, nausea, vomiting
Skin contact :	May cause irritation. Symptoms : redness and pain
Eye contact :	May cause irritation. Symptoms : redness and pain

4.3. Indication of any immediate medical attention and special treatment needed

General Advice : If you feel unwell, seek medical advice (show the label where possible If symptoms persist always call a doctor

SECTION 5: Firefighting measures

5.1. Extinguishing media

foam, carbon dioxide or dry agent

5.2. Special hazards arising from the substance or mixture

Aerosols may explode if heated above 50°C Forms hazardous decomposition products CO.CO2

5.3. Advice for firefighters

Keep container(s) exposed to fire cool, by spraying with water In case of fire, do not breathe fumes



3/9

Safety Data Sheet

Regulation EC No 1907/2006 Art.31

Productname :	Easy Weld	Creationdate :	06.03.13 Version : 2.0
Ref.Nr.:	BDS000994_3_20130306	Replaces:	BDS000994_20111209

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Shut off all ignition sources Ensure adequate ventilation Wear suitable protective clothing and gloves.

6.2. Environmental precautions

Do not allow to enter public sewers and watercourses If polluted water reaches drainage systems or water courses, immediately inform appropriate authorities

6.3. Methods and material for containment and cleaning up

Absorb spillage in suitable inert material

6.4. Reference to other sections

For further information see section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep away from heat and sources of ignition Take precautionary measures against static discharges Equipment should be earthed Use explosion-proof electrical/ventilating/lighting/.../equipment. Use only non-sparking tools. Do not breathe aerosols or vapours. Ensure adequate ventilation Avoid contact with skin and eyes. Wash thoroughly after use Wear protective gloves/protective clothing/eye protection/face protection.

7.2. Conditions for safe storage, including any incompatibilities

Pressurized container : protect from sunlight and do not expose to temperatures exceeding 50°C. Keep out of reach of children.

7.3. Specific end use(s)

Welding Products

SECTION 8: Exposure controls/personal protection

8.1. Control parameters



4/9

Safety Data Sheet	Regulation EC No 1907/2006 Art.31

Productname :	Easy Weld	Creationdate :	06.03.13 Version : 2.0
Ref.Nr.:	BDS000994_3_20130306	Replaces:	BDS000994_20111209

Exposure limits :

Hazardous ingredient	CAS-nr.	method	
EU established exposure limits:			
pentane	109-66-0	TWA	1000 ppm
National established exposure limits, United Kingdom		•	
pentane	109-66-0	TWA	6 <mark>00 ppm</mark>

8.2. Exposure controls

Control procedures :	Ensure adequate ventilation Keep away from heat and sources of ignition Take precautionary measures against static discharges
Personal protection :	Take precautions to avoid contact with skin and eyes when handling the product.
inhalation :	Ensure adequate ventilation
	In case of insufficient ventilation, wear suitable respiratory equipment. Air purifying respirator equiped with organic gas/vapor cartridge (type A or AX)
hands and skin :	Wear suitable protective gloves against chemicals
	(nitrile)
eyes :	Wear safety goggles.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

(for aerosols data for the product Apperance : physical state :	without propellant) Propane/butane propelled liquid.
colour :	Colorless.
odour :	Characteristic odor.
pH :	Not applicable.
Boiling point/range :	35 - 65 °C
Flash point :	< 0 °C
Evaporation rate :	Not available.
Explosion limits : upper limit :	Not available.
lower limit :	Not available.
Vapour pressure :	Not available.
Relative density :	0.728 g/cm3 (@ 20°C).
Solubility in water :	Insoluble in water
Auto-ignition :	> 200 °C
Viscosity :	< 7 mPa.s (@ 40°C).

9.2. Other information

VOC:

510 g/l

SECTION 10: Stability and reactivity



Safety Data Sheet	Regulat

Ref.Nr.: BDS000994_3_20130306 Replaces: BDS000994_20111209
--

10.1. Reactivity

No hazardous reactions known if used for its intended purpose

10.2. Chemical stability

Stable

10.3. Possibility of hazardous reactions

No hazardous reactions known if used for its intended purpose

10.4. Conditions to avoid

Avoid overheating

10.5. Incompatible materials

Strong oxidising agent

10.6. Hazardous decomposition products

CO,CO2

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Inhalation :	Inhalation of solvent vapours may give rise to nausea, headaches and dizziness
Ingestion :	After vomiting of swallowed product aspiration into lungs is likely. Solvents may induce chemical pneumonia.
Skin contact :	Prolonged skin contact will result in defatting of the skin, leading to irritation, and in some cases, dermatitis Repeated exposure may cause skin dryness or cracking.
Eye contact :	May cause irritation.

Toxicological data :

Hazardous ingredient	CAS-nr.	method	
pentane	109-66-0	LD50 oral rat	> 5000 mg/kg
		LD50 derm.rabit	> 3000 mg/kg
Naphtha (petroleum), hydrotreated light	6 <mark>4742-49-0</mark>	LD50 oral rat	> 5000 mg/kg
		LC50 inhal.rat	> 20 mg/l
		LD50 derm.rabit	> 3000 mg/kg



Productname :	Easy Weld	Creationdate :	06.03.13 Version : 2.0
Ref.Nr.:	BDS000994_3_20130306	Replaces:	BDS000994_20111209

SECTION 12: Ecological information

12.1. Toxicity

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Ecotoxicological data:

Hazardous ingredient	CAS-nr.	method	
Naphtha (petroleum), hydrotreated light	64742-49-0	IC50 algae	55 mg/l
		LC50 fish	> 1 mg/l
		EC50 daphnia	3.87 mg/l

12.2. Persistence and degradability

No experimental data available

12.3. Bioaccumulative potential

No experimental data available

12.4. Mobility in soil

Insoluble in water

12.5. Results of PBT and vPvB assessment

No information available

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product :	This material and its container must be disposed of in a safe way. Do not discharge into drains or the environment, dispose to an authorised waste collection point.
Contaminated packaging :	Disposal should be in accordance with local, state or national legislation

SECTION 14: Transport information

14.1. UN number

UN-number: 1950



7 / 9

Safety Data Sheet		Regulation EC No 1907/2006 Art.31			
Productname : Ref.Nr.:	Easy Weld BDS000994_3_201	30306	Creationdate : Replaces:	06.03.13 Version : 2.0 BDS000994_20111209	
14.2. UN proper	shipping name				
Proper ship	pping name:	AEROSOLS			
14.3. Transport	hazard class(es)				
Class: ADR/RID -	Classification code:	2.1 5F			
14.4. Packing gr	oup				
Packing gro	oup:	Not applicable.			
14.5. Environme	ental hazards				
hazardous: IMDG - Ma	rine pollutant: - Environmentally	No No No			
14.6. Special pro	ecautions for user				
ADR/RID - IMDG - Em	Tunnelcode: s:	_(D) F-D, S-U			

ADR/RID - Tunnelcode:	(D)
IMDG - Ems:	F-D, S-U
IATA/ICAO - PAX:	203
IATA/ICAO - CAO	203

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

The Safety Data Sheet is compiled according to the current European requirements. Dir. 2008/47/EC amendment of the aerosol dispenser directive 75/324/EEC. EU-directive 99/45/EC Regulation (EC) No 1907/2006 (REACH)

15.2. Chemical safety assessment

No information available

SECTION 16: Other information

*Explanation risk-phrases:

R11: Highly flammable.



Safety Data Sheet		Regulation EC No 1	Regulation EC No 1907/2006 Art.31	
Productname : Ref.Nr.:	Easy Weld BDS000994_3_20130306	Creationdate : Replaces:	06.03.13 Version : 2.0 BDS000994_20111209	

	R12: Extremely flammable.
	R38: Irritating to skin.
	R65: Harmful: may cause lung damage if swallowed.
	R66: Repeated exposure may cause skin dryness or cracking.
	R67: Vapours may cause drowsiness and dizziness.
	R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in
	the aquatic environment.
*Explanation hazard statements:	H225 : Highly flammable liquid and vapour.
-	H304 : May be fatal if swallowed and enters airways.
	H315 : Causes skin irritation.
	H336 : May cause drowsiness or dizziness.
	H411 : Toxic to aquatic life with long lasting effects.
REVISIONS IN CHAPTRE :	Classification according to 67/548/EEC or 1999/45/EC:
	2.2. Label elements

This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulation.

The information contained herewith is based on the present state of our knowledge and is intended to describe our products from the point of view of safety requirements. It does not guarantee any specific properties. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC.

