

**Productname :** Silicone FG  
**Ref.Nr.:** BDS000340\_3\_20110620

**Creationdate :** 20.06.11 Version : 1.0  
**Replaces:** UK10409

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Silicone FG**  
Aerosol

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Lubricants

### 1.3. Details of the supplier of the safety data sheet

CRC Industries UK Ltd.  
Ambersil House - Wylds Road  
Castlefield Industrial Estate  
TA6 4DD Bridgwater Somerset  
United Kingdom  
Tel.: +44 1278 727200  
Fax.: +44 1278 425644  
E-mail : hse.uk@crcind.com

### 1.4. Emergency telephone number

(+44)(0)1278 72 7200

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification according to 67/548/EEC or 1999/45/EC:

<b>Health:</b>	R67: Vapours may cause drowsiness and dizziness.
<b>Physical:</b>	EXTREMELY FLAMMABLE
<b>Environment:</b>	R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

### 2.2. Label elements

**Warning symbol(s) :** EXTREMELY FLAMMABLE



**Risk-phrase(s) :** R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Ambersil**

Productname : Silicone FG  
 Ref.Nr.: BDS000340\_3\_20110620  
 Creationdate : 20.06.11 Version : 1.0  
 Replaces: UK10409

**Safety-phrase(s) :**

R67: Vapours may cause drowsiness and dizziness.  
 S2: Keep out of the reach of children.  
 S16: Keep away from sources of ignition - No smoking.  
 S23: Do not breathe vapours/spray.  
 S35: This material and its container must be disposed of in a safe way.  
 S51: Use only in well-ventilated areas.

**Extra label elements according to Aerosol Dispenser Directive 75/324/EC:**

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material.  
 Without adequate ventilation formation of explosive mixtures may be possible.

**2.3. Other hazards**

None

**SECTION 3: Composition/information on ingredients****3.1. Substances**

Not applicable.

**3.2. Mixtures**

Hazardous ingredient	CAS-nr.	EC-nr	w/w %	symbol	R-phrases*	Notes
Hydrocarbons, C3-4-rich, petroleum distillate Petroleumgas (1,3-butadiene < 0.1%)	68512-91-4	270-990-9	60-100	F+	12	K
Naphtha (petroleum), hydrotreated light	64742-49-0	265-151-9	<20	F,Xn,N	11-38-51/53-65-67	B,P
<b>Explanation notes</b>						
B : substance with national established workplace exposure limit						
K : not classified as carcinogen, less than 0.1% w/w 1,3-butadiene (Einecs-nr. 203-450-8)						
P : not classified as carcinogen, less than 0.1% w/w benzene (Einecs-nr. 200-753-7)						

Hazardous ingredient	Registration number	CAS-nr.	EC-nr	w/w %	Hazard Class and Category	Hazard statement	Notes
Naphtha (petroleum), hydrotreated light	01-2119484651-34	64742-49-0	265-151-9	<20	Flam. Liq. 2, Skin Irrit. 2, Asp. Tox. 1, STOT SE 3, Aquatic Chronic 2	H225, H315, H304, H336, H411	B, P
<b>Explanation notes</b>							
B : substance with national established workplace exposure limit							
P : not classified as carcinogen, less than 0.1% w/w benzene (Einecs-nr. 200-753-7)							

(\* Explanation phrases : see chapter 16)

**SECTION 4: First aid measures****4.1. Description of first aid measures****Contact with eyes :**

If substance has got into eyes, immediately wash out with plenty of water  
 Seek medical attention if irritation persists

**Productname :** Silicone FG  
**Ref.Nr.:** BDS000340\_3\_20110620

**Creationdate :** 20.06.11 Version : 1.0  
**Replaces:** UK10409

<b>Contact with skin :</b>	Remove contaminated clothing immediately and drench affected skin with plenty of water. Then wash with soap and water Seek medical attention if irritation persists
<b>Inhalation :</b>	Fresh air, keep warm and at rest. Seek medical attention if ill effects occur
<b>Ingestion :</b>	Ingestion is unlikely to occur If swallowed accidentally, do not induce vomiting and seek medical advice.

#### 4.2. Most important symptoms and effects, both acute and delayed

<b>Inhalation :</b>	Excessive inhalation of solvent vapours may give rise to nausea, headaches and dizziness
<b>Ingestion :</b>	May induce chemical pneumonia. Symptoms : sore throat, abdominal pain, nausea, vomiting
<b>Skin contact :</b>	May cause irritation. Symptoms : redness and pain
<b>Eye contact :</b>	May cause irritation. Symptoms : redness and pain

#### 4.3. Indication of any immediate medical attention and special treatment needed

<b>General Advice :</b>	If you feel unwell, seek medical advice (show the label where possible) If symptoms persist always call a doctor
-------------------------	---

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

foam, carbon dioxide or dry agent

#### 5.2. Special hazards arising from the substance or mixture

Aerosols may explode if heated above 50°C  
Forms hazardous decomposition products  
CO,CO2

#### 5.3. Advice for firefighters

Keep container(s) exposed to fire cool, by spraying with water  
In case of fire, do not breathe fumes

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Shut off all ignition sources  
Ensure adequate ventilation  
Wear suitable protective clothing and gloves.

**Productname :** Silicone FG  
**Ref.Nr.:** BDS000340\_3\_20110620

**Creationdate :** 20.06.11 Version : 1.0  
**Replaces:** UK10409

## 6.2. Environmental precautions

Do not allow to enter public sewers and watercourses  
If polluted water reaches drainage systems or water courses, immediately inform appropriate authorities

## 6.3. Methods and material for containment and cleaning up

Absorb spillage in suitable inert material  
Place in appropriate container

## 6.4. Reference to other sections

For further information see section 8

# SECTION 7: Handling and storage

## 7.1. Precautions for safe handling

Keep away from heat and sources of ignition  
Take precautionary measures against static discharges  
Equipment should be earthed  
Use explosion-proof electrical/ventilating/lighting/?/equipment.  
Use only non-sparking tools.  
Do not breathe aerosols or vapours.  
Ensure adequate ventilation  
Avoid contact with skin and eyes.  
Wash thoroughly after use  
Wear protective gloves/protective clothing/eye protection/face protection.

## 7.2. Conditions for safe storage, including any incompatibilities

Pressurized container : protect from sunlight and do not expose to temperatures exceeding 50°C.  
Keep in a cool, dry, well ventilated place  
Keep out of reach of children.

## 7.3. Specific end use(s)

Lubricants

# SECTION 8: Exposure controls/personal protection

## 8.1. Control parameters

### Exposure limits :

No information available

## 8.2. Exposure controls

**Productname :** Silicone FG  
**Ref.Nr.:** BDS000340\_3\_20110620

**Creationdate :** 20.06.11 Version : 1.0  
**Replaces:** UK10409

<b>Control procedures :</b>	Ensure adequate ventilation Keep away from heat and sources of ignition Take precautionary measures against static discharges
<b>Personal protection :</b>	Take precautions to avoid contact with skin and eyes when handling the product. Ensure adequate ventilation
<b>inhalation :</b>	In case of insufficient ventilation, wear suitable respiratory equipment. Air purifying respirator equipped with organic gas/vapor cartridge (type A or AX)
<b>hands and skin :</b>	Wear suitable protective gloves (nitrile)
<b>eyes :</b>	Wear safety goggles.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Apperance : physical state :</b>	Propane/butane propelled liquid.
<b>colour :</b>	Colorless.
<b>odour :</b>	Solvent.
<b>pH :</b>	Not applicable.
<b>Boiling point/range :</b>	Not available.
<b>Flash point :</b>	< 0 °C
<b>Evaporation rate :</b>	Not available.
<b>Explosion limits : upper limit :</b>	Not available.
<b>lower limit :</b>	Not available.
<b>Vapour pressure :</b>	Not available.
<b>Relative density :</b>	0.71 (@ 20°C).
<b>Solubility in water :</b>	Insoluble in water
<b>Auto-ignition :</b>	> 200 °C
<b>Viscosity :</b>	< 7 mPa.s (@ 40°C).

### 9.2. Other information

**VOC:** 545 g/l

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No hazardous reactions known if used for its intended purpose

### 10.2. Chemical stability

Stable

### 10.3. Possibility of hazardous reactions

No hazardous reactions known if used for its intended purpose



**Productname :** Silicone FG  
**Ref.Nr.:** BDS000340\_3\_20110620

**Creationdate :** 20.06.11 Version : 1.0  
**Replaces:** UK10409

#### 10.4. Conditions to avoid

Avoid overheating

#### 10.5. Incompatible materials

Strong oxidising agent

#### 10.6. Hazardous decomposition products

CO,CO2

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

<b>Inhalation :</b>	Inhalation of solvent vapours may give rise to nausea, headaches and dizziness
<b>Ingestion :</b>	May cause gastrointestinal disturbances
<b>Skin contact :</b>	Prolonged skin contact will result in defatting of the skin, leading to irritation, and in some cases, dermatitis
	Repeated exposure may cause skin dryness or cracking.
<b>Eye contact :</b>	May cause irritation.

#### Toxicological data :

No information available

### SECTION 12: Ecological information

#### 12.1. Toxicity

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

#### Ecotoxicological data:

No information available

#### 12.2. Persistence and degradability

No experimental data available

#### 12.3. Bioaccumulative potential

No experimental data available

#### 12.4. Mobility in soil

**Productname :** Silicone FG  
**Ref.Nr.:** BDS000340\_3\_20110620

**Creationdate :** 20.06.11 Version : 1.0  
**Replaces:** UK10409

Insoluble in water

#### 12.5. Results of PBT and vPvB assessment

No information available

#### 12.6. Other adverse effects

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

**Product :** This material and its container must be disposed of in a safe way.  
Do not discharge into drains or the environment, dispose to an authorised waste collection point.  
**Contaminated packaging :** Disposal should be in accordance with local, state or national legislation

### SECTION 14: Transport information

#### 14.1. UN number

UN-number : 1950

#### 14.2. UN proper shipping name

Proper shipping name: AEROSOLS, flammable

#### 14.3. Transport hazard class(es)

Class: 2.1  
ADR/RID - Classification code: 5F

#### 14.4. Packing group

Packing group: Not applicable.

#### 14.5. Environmental hazards

ADR/RID - Environmentally hazardous: No  
IMDG - Marine pollutant: No  
IATA/ICAO - Environmentally hazardous: No

#### 14.6. Special precautions for user

ADR/RID - Tunnelcode: (D)  
IMDG - Ems: F-D,S-U



**Productname :** Silicone FG  
**Ref.Nr.:** BDS000340\_3\_20110620

**Creationdate :** 20.06.11 Version : 1.0  
**Replaces:** UK10409

IATA/ICAO - PAX: 203  
IATA/ICAO - CAO 203

#### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

The Safety Data Sheet is compiled according to the current European requirements.  
Dir. 2008/47/EC amendment of the aerosol dispenser directive 75/324/EEC.  
EU-directive 99/45/EC  
Regulation (EC) No 1272/2008  
Regulation (EC) No 1907/2006 (REACH)

#### 15.2. Chemical safety assessment

No information available

### SECTION 16: Other information

\*Explanation risk-phrases: R11: Highly flammable.  
R12: Extremely flammable.  
R38: Irritating to skin.  
R65: Harmful: may cause lung damage if swallowed.  
R67: Vapours may cause drowsiness and dizziness.  
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

\*Explanation hazard statements: H225 : Highly flammable liquid and vapour.  
H304 : May be fatal if swallowed and enters airways.  
H315 : Causes skin irritation.  
H336 : May cause drowsiness or dizziness.  
H411 : Toxic to aquatic life with long lasting effects.

This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulation.

The information contained herewith is based on the present state of our knowledge and is intended to describe our products from the point of view of safety requirements. It does not guarantee any specific properties.

Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC.