# **Technical Data**





**AMBERGREASE FG2** is designed as a high temperature resistant, food grade grease, containing PTFE anti-wear and other additives all of which are FDA listed. Suitable for all plain and anti-friction bearings as well as sliding surfaces. Resistant to a wide range of chemical cleaning solutions used in the food and drink industries.

### **COST SAVING BENEFITS**

Provides long term lubrication at high temperatures, extending lubrication intervals

- 1. Greatly reduced formation of carbon deposits associated with many high temperature greases
- Good sealing properties protect components working in wet environments from corrosion
- 3. PTFE solid lubricant improves anti-wear performance prolonging component life
- 4. Does not effect most rubber type sealing materials

## **METHOD OF APPLICATION**

Ambergrease FG2 can be applied by hand, or by using a standard grease gun (400gm cartridge)

# **TECHNICAL DATA**

NSF Registered, Category : H1

NSF Registration No. : 138265

Appearance : White semi-translucent grease

NLGI Classification : 2

Thickener : Silica

Drop Point (IP 132) : None

Base Oil : High viscosity silicone oil

Solid Lubricant : PTFE Copper Corrosion (IP112) : Negative Water Washout (ASTM D1264) @  $38\,^{\circ}$ C : < 2% max.

Dynamic Corrosion Resistance (EMCOR) : 0:0

(IP 220)

Shell Four Ball (IP239) Weld Load : 180kg
Mean Hertz Load : 30kg
dN Factor : 200,000

Operating Temperature Range : -20°C to +220°C

Packaging : 400g cartridge

All ingredients are FDA listed. Ambergrease FG2 is NSF H1 registered and meets the USDA 1998 H1 Guidelines. This product contains no genetically modified ingredients and does not contain any nut oil or derivatives

Based upon the present state of our knowledge and information received from our suppliers, evaluation of this product indicates that it is free from nut oils and their derivatives

## **STORAGE**

The product may be stored at normal ambient temperatures and has a shelf life of not less than 36 months with correct storage. Aerosols should always be stored below  $50^{\circ}$ C, away from direct heat and naked flame.

#### **HEALTH AND SAFETY**

Health and Safety sheet available separately.

## MISREPRESENTATION ACT 1967 TRADE DESCRIPTIONS ACT 1968

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

CRC Industries UK Limited, Wylds Road, Bridgwater, Somerset, TA6 4DD

Tel: +44 (0) 1278 727200 Fax: +44 (0) 1278 425644

Web: www.ambersil.com E-mail: sales.uk@crcind.com