Technical Data







BIOWELD is a unique water based spatter release agent, **presented in aerosol**. It has been developed specifically to exclude the use of all harmful solvents, silicones and oils.

APPLICATIONS

Bioweld is completely odourless, non-flammable and safe in use. The fine spray pattern ensures total control and economical coverage when applying the product. Ideal for use in numerous industries:

Automotive Manufacture and Repair

Office Furniture

• Shipbuilding and Dockyards

Tool Manufacturers

Heavy Plant Manufacture

• Agriculture

Construction

Fork Lift Trucks

Prevents spatter adhesion on welding equipment, workpieces, surfaces, jigs and surrounding areas. Apply a light, even film from 9"-12" (25 - 30 cm). Do not overapply.

After welding, the film can be wiped away very easily and leaves no residues. Post-welding applications (e.g. painting, hot dip galvanising) can then be carried out without interference.

TECHNICAL DATA

Appearance : Clear, colourless liquid

Odour : Negligible

SG @ 25°C : 1.039

Pressure @ 25°C : 5 Bar

Discharge rate : 0.9 g/sec

pH : 9.7

Solubility : Soluble in water

Flammability : Non-flammable

Flashpoint : Not applicable in sealed aerosol

Packaging : 400 ml aerosol (12 per carton), 5ltr,

25ltr and 200ltr

STORAGE

The product may be stored at normal ambient temperatures and has a shelf life of not less than 72 months with correct storage. Aerosols should always be stored below 50° C, away from direct heat and naked flame.

HEALTH AND SAFETY

Health and Safety sheet available separately.

TECHNICAL SERVICE

CRC Industries UK Ltd provides a technical support service and maintains a constant programme of research and development. We are able to assist customers by specific product development to meet particular requirements.

MISREPRESENTATION ACT 1967 TRADE DESCRIPTIONS ACT 1968

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

CRC Industries UK Ltd, Wylds Road, Bridgwater, Somerset, TA6 4DD, UK.

Tel: +44 (0) 1278 727200 Fax: +44 (0) 1278 425644

Web: www.ambersil.com E-mail: sales.uk@crcind.com